

Pure Water on Tap

D5 SERIES



- The most reliable POU cooler on the market
- Available in bench top or floor standing
- Connects to mains water supply
- Hot & Cold or Cool & Cold models available
- HUGE 14.3L Cold Tank
- Compatible with most Inline Filter Systems
- Easy to clean and sanitise
- 36 Month Comprehensive Warranty



Pure Water on Tap

GENERAL FEATURES

Waterworks™ has been leading the way with POU water coolers since introducing the D5 series, over 20 years ago. This model has often been "copied" but none have been able to equal or better the quality and longevity of the Waterworks™ D5.

COLD TANK: Huge 14.3 litre high density polypropylene tank. The tank is tough, rustproof and is easy to clean with its large radius.

HOT TANK: 1.8 litre, type 304 stainless steel with 500 watt sheathed heater ensures temperature control. On/ off switch is easily accessible at the back of the unit.

CABINET: Gloss Cloud White colour. Top and front panels are moulded UV treated ABS. Side panels are zinc coated steel sheets, covered in polymer polyester resin.

TAPS: NSF approved, durable polypropylene lever type taps with self-closing design and fast flow. How safety tap comes as standard on hot/ cold model. Optional push taps now available.

FLOAT ASSEMBLY: One stage polyethylene float system maintains the water level and shuts off when full.

OPTIONAL EXTRAS

PNP FILTER SYSTEM: The Waterworks™ PNP filter range are available in single, twin or triple. With the swing & twist design and automatic water shutoff, filter changes are simple, no need for tools or to turn off the mains water.

CD2 – CUP DISPENSER: The CD2 is perfectly colour matched to suit the B5, B10, D5 & D10 coolers. Waterworks™ paper \$plastic cups are made to fit the CD2.

SPECIFICATIONS

REFRIGERATION: Gas R134A. The refrigerant flow is controlled by a capillary tube which has no moving parts. The compressor is hermetically sealed with an automatic overload protector. Lubricant is not needed.

ELECTRICAL: Certificate power number 160793. 220v 50Hz single phase. A 1.5 metre power cord is supplied. Full load current is 1.2 amps.

CONDENSER: Quietly operating, air cooled with no moving parts.

PERFORMANCE

Tap 1 Approx. 4-10°C
Tap 2 Room Temperature
Hot tap Approx. 84-89°C

CAPACITY

ROOM TEMP	150ML CUPS/HR AT 10°C	LITRES/HR AT 10°C
21°C	44	6.6
27°C	32	4.8
32°C	18	2.7

SHIPPING WEIGHTS & DIMENSIONS

MODEL	WEIGHT	MODEL	WEIGHT	WIDTH	DEPTH	HEIGHT
D5C	19kg	D5CH	21kg	33cm	33cm	115cm
SD5C	16kg	SD5CH	18kg	33cm	33cm	70cm

WARRANTY

The Waterworks™ D5 series is covered by our 36 month Comprehensive Warranty (copy available on request). The warranty provides comprehensive parts and labour coverage, for the period of 36 months from the date of original sale.