

Pure Water on Tap

An innovative product that kills over 99.9 % of all E.coli, viruses and other bacteria in your rainwater

Ensuring your stored water supply is safe for consumption can be a tricky task. Water captured on rooftops can easily be contaminated as debris easily washes into the tank during a down pour.

Drinking this untreated water can be unsafe and lead to illness. Treating water is essential to ensure good health for you and your family.

TankSafe™ is an alternative to dosing with chlorine. It is tasteless, odourless and chlorine free, designed specifically for tank water disinfection. TankSafe™ is low cost and non-toxic.

While most chemicals used for water disinfection are toxic (some are even known carcinogens), **TankSafe™** will stay in your tank and keep it protected from bacteria and pathogens for up to 2 months.

Why treat your tank water?

Unfortunately, whilst rainwater starts out pristine, it is quickly contaminated and by the time it reaches our taps it is often unsafe to drink because micro-organisms from animal and bird droppings, decaying vegetable matter and dirt can contaminate the water.

There are always low levels of bacteria in tank water and if left without treatment these levels can get out of control – you get smelly, stagnant water which is unsafe to drink.

Available in
1, 2, 5 and 15 Litres



Disinfects up to 240,000 Litres of Rainwater*

Pure Water on Tap

Your Solution for all types of stored water!

Rainwater, carted water and water that is pumped up from bores and dams all have the potential to be unsafe.

The TankSafe™ formula can vastly improve the safety of these water supplies.



How do you know TankSafe™ is working?

Pour the required amount of TankSafe™ in your rainwater tank. Test 24 hours after dosing with TankSafe™ to ensure appropriate dosing has taken place.

LEVEL OF PROTECTION



To check levels of protection after dosing, immerse a TankSafe™ test strip in the treated water for 2 sec and let the strip sit for 30 sec, then compare to the colour chart indicator.

To ensure continuous safety, test a minimum of every 2-3 weeks or after a significant rainfall.



Standard Dosage Chart

Volume of water to be treated	Required dosage of TankSafe™
1,000 L	65 ml.
5,000 L	330 ml.
10,000 L	650 ml.
32,000 L	2,000 ml.
80,000 L	5,000 ml.
240,000 L	15,000 ml.

Recommended dosage is 65 ml. per 1000 litres of tank volume, depending on the pollution grade.

Follow the table to find the correct dosage for your water volume.

Requires 24 hour contact time